



Typ USE-1

Domestic hot water heater exclusively stainless steel to ANSI 316L / 316 Ti

From 150 to 1000 liter

- For use with district heating, solar, boilers, and condensing technology
- With an internal smooth pipe register
- Corrosion resistant
- Connection for electric heater G 1 1/2"
- Thermostat connection G 1/2"
- Heating in the lower ground area also
- Hygienic through smooth pipe register

Designed, manufactured and tested according to DIN 4753, DIN EN 12897, and company standards in addition to PED-European Equipment Directive. Production monitored and certified by TÜV Rheinland. TIG but-welded with no crease. Complete tank dip-pickled and passivated.


Operating pressure	max. 10 bar
Operating pressure smooth pipe register	max. 25 bar
Operating temperature	max. 95°C
Operating temperature smooth pipe register	max. 200°C

Accessories - optional:

- Dipping sleeve G 1/2" made out of stainless steel ANSI 316 Ti, L = 200 mm
- Thermometer
- Flange cover with G 1 1/2" connection for electric heater
- Screw-in heater 12 kW
- Flange heater 15 kW


Insulation:

- 100 mm covered with PS-jacket
- colour RAL 9022 silver
- other colours on demand
- fire classification B2
- CE-marking
- CFC-free
- 100 % recyclable



European energy label

Best Deal - STAINLESS STEEL



Head quarter:


DINOX-D®
 Edelstahlprodukte GmbH
 Im Hegen 14 a
 D-22113 Oststeinbek
 Tel. +49(0)40-71 39 09-28
 Fax +49(0)40-71 39 09-87
 info@dinox-d.de
 www.dinox-d.de

Technical Department:

D-23970 Wismar
 Tel. +49(0)38 41-303 48-0
 Fax +49(0)38 41-303 48-29
 technik@dinox-d.de



Domestic hot water heater exclusively stainless steel to ANSI 316L / 316 Ti



Energy related Product (ErP) Directive

Product data sheet

Acc. to (1) Commission Regulation (EU)
No 814/2013: „ecodesign requirements of“

(2) Commission deligated regulation (EU)
No 812/2013: „Energy labelling“ of
water heaters and hot water storage tanks.

- max. operating pressure: 10 bar
- max. operating pressure smooth pipe register: 25 bar
- max. operating temperature: 95°C
- max. operating temperature smooth pipe register: 200°C***
- with an internal smooth pipe register
- all connections acc. to ISO 228-1
- Insulation:
 - 100 mm covered with PS-jacked
 - colour RAL 9022 silver
 - other colours on demand
 - fire classification B2
 - CE-marking
 - CFC free
 - 100 % recyclable
- USE1 150 thermostat- and thermometer connections are placed 180° offset
- subject to technical changes

Capacity	150	200	300	400	500	600	750	1000
Measures in mm								
H1	65	65	65	70	70	70	80	70
H2	260	305	305	330	330	350	380	405
H3	685	605	795	890	890	910	940	1005
H4	760	685	870	975	975	995	1025	1140
H5	1130	1145	1375	1420	1670	1690	1720	1745
H6	1313	1362	1612	1657	1907	1929	1989	2032
H7	340	365	365	390	390	410	440	465
H8	500	500	600	600	600	620	700	700
H9	760	685	870	975	975	995	1025	1140
H10	1130	1145	1375	1420	1670	1690	1720	1745
H total with insulation	1446	1495	1745	1790	2040	2079	2123	2166
Diagonal height without insulation ±5	1335	1385	1635	1680	1925	1955	2020	2075
D1 diameter without insulation	400	500	500	600	600	650	750	850
D2 diameter with insulation	600	700	700	800	800	850	950	1050
Weight (kg)	37	45	61	76	82	101	129	168
Energy efficiency class	B	B	B	B	B	B	C	C
Standing losses „S“ in Watt/h	41	47	56	68	78	86	102	119

Connections

Inspection flange*	120/180	120/180	120/180	120/180	120/180	120/180	120/180	120/180
Cold and hot water	G 1"	G 1½"	G 1½"					
Circulation return	G ¾"							
Thermostat	G ½"							
Thermometer	G ½"							
Venting	G 1"							
Electric heater	G 1½"							
Heating register	AG 1"	AG 1"	AG 1¼"	AG 1½"				
Heating surface in m²	0,9	0,9	1,4	1,8	1,8	1,8	2,4	2,8

Performance data

Performance factor acc. to DIN 4708	2	4	12	20	23	26	35	46
Continuous Performance ** Liter/h	926	978	1522	1743	1924	2012	2413	2846

* special equipment for electric heater: Flange cover with sleeve G 1 ½", ** during 10/80/45°C, *** Operating medium register: liquid state, not hazardous to health